

Safety Data Sheet

Issue date 10-May-2019 Version 2

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product name CHAMPION SPRAYON FRESH CARPET DEODORIZING MOUSSE

Chemical name 7-7866-2

Other means of identification

Product code FG 438-5147-4 **Synonyms** Carpet deodorizer

Recommended use of the chemical and restrictions on use

Recommended UseTo remove bad odors from carpets.

Uses advised against DO NOT USE ON FLOORS Do not use to clean glass or wood surfaces.

Details of the supplier of the safety data sheet

Supplier AddressManufacturer AddressChase Products Co.Chase Products Co.2727 Gardner Road2727 Gardner RoadBroadview, IL 60155Broadview, IL 60155708-865-1000708-865-1000

Emergency Telephone Number

Company Phone Number 708-865-1000 **24 Hour Emergency Phone Number** 1-800-255-3924

Emergency telephone ChemTel 1-800-255-3924

2. Hazards Identification

Classification

Serious eye damage/eye irritation	Category 2
Gases Under Pressure	liquefied gas
FLAMMABLE AEROSOLS	Category 1

Label Elements

EMERGENCY OVERVIEW

DANGER

hazard statements

Causes serious eye irritation

Contains gas under pressure; may explode if heated

EXTREMELY FLAMMABLE AEROSOL



Appearance Cloudy, light yellow liquid

Physical State Aerosol

Odor Perfumed.

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Wear eye protection.

Keep away from heat, sparks, open flames and hot surfaces. — No smoking

Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Precautionary Statements - Storage

Protect from sunlight. Store in a well-ventilated place Do not expose to temperatures exceeding 122 °F (50 °C)

Hazards not otherwise classified (HNOC)

Other Information

Harmful to aquatic life with long lasting effects

-

3. Composition/information on Ingredients

Common Name Carpet deodorizer.
Synonyms Carpet deodorizer.
Chemical Family MIXTURES.
Formula 7-7866-2

Chemical nature Aqueous solution of surfactants and solvents.

Chemical name	CAS No	weight-%	Trade secret
Water	7732-18-5	70-75	*
Ethyl alcohol	64-17-5	5-10	*
Acetone	67-64-1	5-10	*
N-Butane	106-97-8	1-5	*
Propane	74-98-6	1-5	*

Chemical Additions

Hazardous components according to OSHA, are listed when present at 1% or greater. Carcinoges are listed when present at 0.1% or greater.

4. First aid measures

FIRST AID MEASURES

Eye Contact Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact

lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control

center or doctor for treatment advice.

Skin contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

physician.

Inhalation If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an

ambulance, then provide artifical respiration, preferably mouth-to-mouth, if possible. Call a

poison control center or doctor for further treatment advise.

Ingestion Ingestion from an aerosol product is unlikely to occur.

Most important symptoms and effects, both acute and delayed

Symptoms Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

and nausea. Prolonged and repeated contact with skin may cause irritation and reddening. Contact with eyes causes irritation.

Indication of any immediate medical attention and special treatment needed

Note to physicians None needed.

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may release carbon monoxide and carbon dioxide.

Explosion data

Sensitivity to Mechanical Impact Contents under pressure, keep away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautionsUse with adequate general or local exhaust ventilation.

For emergency responders Remove all sources of ignition.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert,

absorbent material.

Methods for cleaning upClean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handlingDo not deliberately inhale vapor or spray mist. Avoid getting spray into eyes.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store in a cool, dry place away from heat and open flame. Keep out of reach of children.

AEROSOL STORAGE LEVEL I (NFPA-30B).

Incompatible MaterialsAvoid heat, open flame and contact with strong alkali and strong oxidizing agents.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethyl alcohol	STEL: 1000 ppm	TWA: 1000 ppm	IDLH: 3300 ppm
64-17-5		TWA: 1900 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1900 mg/m ³
		(vacated) TWA: 1900 mg/m ³	
Acetone	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 250 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	
		(vacated) STEL: 2400 mg/m ³	
		The acetone STEL does not	
		apply to the cellulose acetate	
		fiber industry. It is in effect for all	
		other sectors.	
		(vacated) STEL: 1000 ppm	
N-Butane	STEL: 1000 ppm explosion	(vacated) TWA: 800 ppm	IDLH: 1600 ppm
106-97-8	hazard	(vacated) TWA: 1900 mg/m ³	TWA: 800 ppm
			TWA: 1900 mg/m ³
Propane	: See Appendix F: Minimal	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6	Oxygen Content, explosion	TWA: 1800 mg/m ³	TWA: 1000 ppm
	hazard	(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	

Appropriate engineering controls

Engineering controlsUse with adequate general or local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face Protection Conventional eyeglasses to guard against splashing.

Skin and Body Protection Household type gloves, recommended.

Respiratory protection None required if used in a well-ventilated area . Follow label directions and precautions for

the correct use of the product.

General hygiene considerations Wash hands thoroughly after handling.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Aerosol

Appearance Cloudy, light yellow liquid Odor Perfumed.

Color light yellow Odor threshold No information available

PropertyValuesRemarks • MethodpH7.25 +/- 0.3No information availableMelting point/freezing pointNot applicableNo information availableBoiling point/boiling rangeWater 212 °F/100 °CNo information availableFlash PointNot Available. This is an aerosolNo information available

product for which Flame Projection is 0 inches. Temperatures above 120 °F may cause cans to burst. Not

applicable. This is an foam aerosol that when tested for flammability the flame duration is 7 seconds or more and the

flame height is 4 cm or more.

Evaporation Rate Faster than butyl acetate No information available

Flammability (solid, gas) No information available Flammability Limits in Air No information available

Upper flammability limits Not available **Lower Flammability Limit** Not available

No information available Vapor pressure **Vapor Density** No information available

Relative Density 0.965 to 0.980 concentrate No information available

Water solubility Soluble in water

Solubility in other solvents No information available No information available Partition coefficient **Autoignition Temperature** No information available **Decomposition temperature** No information available No information available Kinematic viscosity **Dynamic viscosity** No information available

No information available **Explosive properties Oxidizing properties** No information available

Other Information

Softening point No information available No information available Molecular weight

VOC content (%) 14.88

Density 8.03 to 8.16 lb/gal No information available **Bulk Density**

10. Stability and Reactivity

Reactivity

Not applicable Not applicable

Chemical stability

Stable.

Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures above 122 °F (50 °C).

Incompatible Materials

Avoid heat, open flame and contact with strong alkali and strong oxidizing agents.

Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide and carbon dioxide.

11. Toxicological Information

Information on likely routes of exposure

Product Information Primary routes of entry: Eye contact, skin contact, inhalation, ingestion (possible, but

consider unlikely).

Inhalation Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and

nausea.

Can cause irritation after contact with eyes. **Eye Contact**

Skin contact May cause irritation.

Ingestion

This is an aerosol product, ingestion is unlikely to occur.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Water	> 90 mL/kg (Rat)	-	-
7732-18-5			
Ethyl alcohol	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
64-17-5			
Acetone	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h
67-64-1			- '
N-Butane	-	-	= 658 g/m ³ (Rat) 4 h
106-97-8			
Propane	-	-	> 800000 ppm (Rat) 15 min
74-98-6			

Information on toxicological effects

Symptoms Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and

nausea.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritating to eyes.

Skin corrosion/irritation May cause skin irritation and reddening after prolonged or repeated contact with skin.

Serious eye damage/eye irritation

corrosivity Not applicable.
sensitization No a skin sensitizer.
Germ cell mutagenicity No information available.

Carcinogenicity Not known chronic effects based on available data. None of the ingredients present in

excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.

Chemical name	ACGIH	IARC	NTP	OSHA
Ethyl alcohol	A3	Group 1	Known	X
64-17-5		-		

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Aspiration Hazard Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and

nausea.

Numerical measures of toxicity - Product Information

Unknown acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 36903 mg/kg
ATEmix (dermal) 39474 mg/kg
ATEmix (inhalation-gas) 5922156 mg/l
ATEmix (inhalation-dust/mist) 644.8 mg/l
ATEmix (inhalation-vapor) 1150 mg/l

12. Ecological Information

ecotoxicity

6.1 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			Microorganisms	
Ethyl alcohol		100: 96 h Pimephales	EC50 = 34634 mg/L 30 min	2: 48 h Daphnia magna
64-17-5		promelas mg/L LC50 static	EC50 = 35470 mg/L 5 min	mg/L EC50 Static 9268 -
		13400 - 15100: 96 h	_	14221: 48 h Daphnia magna
		Pimephales promelas mg/L		mg/L LC50 10800: 24 h
		LC50 flow-through 12.0 -		Daphnia magna mg/L EC50
		16.0: 96 h Oncorhynchus		
		mykiss mL/L LC50 static		

Acetone		6210 - 8120: 96 h	EC50 = 14500 mg/L 15 min	10294 - 17704: 48 h
67-64-1	Pi	mephales promelas mg/L		Daphnia magna mg/L EC50
		LC50 static 8300: 96 h		Static 12600 - 12700: 48 h
	Le	epomis macrochirus mg/L		Daphnia magna mg/L EC50
		LC50 4.74 - 6.33: 96 h		
	Or	ncorhynchus mykiss mL/L		
		LC50		

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Ethyl alcohol 64-17-5	-0.32
Acetone 67-64-1	-0.24
N-Butane 106-97-8	2.89
Propane 74-98-6	2.3

Other adverse effects

No information available

13. Disposal Considerations

Waste treatment methods

Disposal of wastes

Dispose of in accordance with federal, state and local regulations.

Contaminated packaging

Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone		Included in waste stream:		U002
67-64-1		F039		

Chemical name	California Hazardous Waste Status	
Ethyl alcohol	Toxic	
64-17-5	Ignitable	
Acetone	Ignitable	
67-64-1		

14. Transport Information

DOT

UN/ID no Limited Quantity
Proper Shipping Name Consumer Commodity

Hazard Class ORM-D

IATA

UN/ID no UN1950

Proper Shipping Name Aerosols, flammable

2.1

Hazard Class

IMDG

UN/ID no UN1950

Proper Shipping Name Aerosols, flammable

Hazard Class 2.1

Marine pollutant This product does not contain marine pollutants.

15. Regulatory information

International Inventories

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic

Subtances Control Act (TSCA) Chemical Substance Inventory.

DSL All ingredients are listed or are excluded from listing on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

This product does not contain toxic chemicals (above the de minimis level) subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

SARA 311/312 Hazard Categories

Acute Health Hazard yes
Chronic Health Hazard No
Fire Hazard No
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb		RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Water			X
7732-18-5			
Ethyl alcohol	X	X	X
64-17-5			
Acetone	X	X	X
67-64-1			
N-Butane	X	X	X
106-97-8			
Propane	X	X	X
74-98-6			

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information				
NFPA	Health Hazards 2	Flammability 1	Instability 1	Physical and chemical properties Not applicable
HMIS	Health Hazards 2	Flammability 2	Physical hazards 1	Personal Protection B - Eyes and hands protection

Issue date 10-May-2019

Revision note

This SDS supersedes a previous SDS dated December 19, 2014.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet