# **CL948** TECHNICAL DATA SHEET HEAT STABLE SILICONE RELEASE AGENT

## **PRODUCT DESCRIPTION:**

- Stops sticking
- Anti corrosive
- Waterproof
- Safe for use on food packaging & processing equipment

.....

NSF Registered

Use as a lubricant, release agent, water repellent, and protective coating. The dry Silicone film is non-flammable, colorless, non-staining, waxless, and heat-stable; unaffected by temperatures ranging from -40°C (-40°F) to over 200°C (392°F).

#### AREAS OF USE:

Use on such equipment as ovens, freezers, conveyors, belts and chutes. Proper use of Silicone Spray minimizes clean-up time, speeds equipment disassembly, stops sticking and binding, protects equipment, and increases production. Use on cool ovens ONLY. Avoid spraying pilot light.

#### SPECS:

Can Size: 20 oz. Net Weight: 11 oz. Shipping Weight: 13 Lbs. Packaged: 12 cans per case UPC Number: 7 13014 11948 3 Product Number: CL948 Extender Tube: N

## **REGULATORY:**

Ozone Depleting Compounds: None Recyclable Package: Yes VOC Compliant CARB: Yes VOC Compliant OTC: Yes Flammability: Flammable

# PHYSICAL CHARACTERISTICS:

Color: Colorless Fragrance: Mild petroleum Shelf Life: 1 year +

See label side panel for First Aid and additional Precautionary Statements 24 HOUR MEDICAL EMERGENCY NUMBER: 1-866-836-8855

.....

KEEP OUT OF REACH OF CHILDREN CONSULT SDS BEFORE USING





Federal regulations prohibit CFC propellants in aerosols.



