claire.

SAFETY DATA SHEET

1. Identification

Product number 1000000962

Product identifier 14 OZ CLAIRE ANTISTATIC SPRAY LB 12PK

Revision date 02-26-2019

Company information Claire Manufacturing Co.

1000 Integram Dr

Pacific, MO 63069 United States

Company phone General Assistance 1-630-543-7600

Emergency telephone US 1-866-836-8855 Emergency telephone outside 1-952-852-4646

US

Version # 04

Supersedes date 05-25-2016
Recommended use COATING
Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

Health hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Response Wash hands after handling.

Storage Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Ethyl Alcohol		64-17-5	60 - 80
1,1-difluoroethane		75-37-6	20 - 40
Quaternary Ammonium Compounds, Bis(hydrogenated Tallow Alkyl)dimethyl, Chlorides		61789-80-8	0.1 - 1
Other components below reportal	ole levels		1 - 2.5

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Product #: 1000000962 Version #: 04 Revision date: 02-26-2019 Issue date: 08-10-2015

4. First-aid measures

Inhalation If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Eve contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur. Headache. Coughing.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to **General information**

Alcohol resistant foam. Powder. Carbon dioxide (CO2).

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire fighting

equipment/instructions

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move Specific methods containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

General fire hazards Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Level 2 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame. heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

Product name: 14 OZ CLAIRE ANTISTATIC SPRAY LB 12PK

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Ethyl Alcohol (CAS 64-17-5)	PEL	1900 mg/m3	
•		1000 ppm	
US. ACGIH Threshold Limit Values	:		
Components	Туре	Value	
Ethyl Alcohol (CAS 64-17-5)	STEL	1000 ppm	
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	
Ethyl Alcohol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	
US. Workplace Environmental Exp	osure Level (WEEL) Guides		
Components	Туре	Value	
1,1-difluoroethane (CAS 75-37-6)	TWA	2700 mg/m3	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

1000 ppm

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing.

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Gas. Aerosol. **Form** Not available. Color Odor Not available. **Odor threshold** Not available. Not available. pН Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

Flash point -58.0 °F (-50.0 °C) PROPELLANT estimated

Evaporation rateNot available.Flammability (solid, gas)Not available.Upper/lower flammability or explosive limits

Flammability limit - lower 4.2 % estimated

(%)

Flammability limit - upper

16.9 % estimated

Explosive limit - lower (%)

Not available. Not available.

Explosive limit - upper (%) Vapor pressure

41 psig @70F estimated

Vapor density

Not available.

Relative density

0.812 g/cm3 estimated

Solubility(ies)

Solubility (water) **Partition coefficient**

Not available. Not available.

(n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Explosive properties

Heat of combustion (NFPA

30B)

20.69 kJ/g estimated

Not explosive.

Oxidizing properties Not oxidizing. 0.812 estimated Specific gravity

VOC (Weight %) 79.44 %

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected. Skin contact No adverse effects due to skin contact are expected. Direct contact with eyes may cause temporary irritation. Eye contact

Expected to be a low ingestion hazard. Ingestion

Species

Rat

Symptoms related to the physical, chemical and toxicological characteristics Headache. Coughing.

Information on toxicological effects

Acute toxicity Components

Ethyl Alcohol (CAS 64-17-5)		
<u>Acute</u>		
Inhalation		
LC50	Cat	85.41 mg/l, 4.5 Hours
		43.68 mg/l, 6 Hours
	Mouse	> 60000 ppm
		79.43 mg/l, 134 Minutes

Test Results

> 115.9 mg/l, 4 Hours

Components	Species	Test Results
		51.3 mg/l, 6 Hours
Oral		
LD50	Monkey	6000 mg/kg
	Mouse	10500 ml/kg
	Pig	> 5000 mg/kg
	Rat	10470 mg/kg
		7800 ml/kg

Quaternary Ammonium Compounds, Bis(hydrogenated Tallow Alkyl)dimethyl, Chlorides (CAS 61789-80-8)

Acute Dermal

LD50 Rat > 2000 mg/kg, 24 Hours

Inhalation

LC50 Rat > 180 mg/l, 60 Minutes

Oral

LD50 Rat > 2000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Not likely, due to the form of the product. **Aspiration hazard**

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Test Results Species** Ethyl Alcohol (CAS 64-17-5) Aquatic

Crustacea EC50 Water flea (Daphnia magna) 7700 - 11200 mg/l, 48 hours Fish LC50 Fathead minnow (Pimephales promelas) > 100.1 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

^{*} Estimates for product may be based on additional component data not shown.

^{*} Estimates for product may be based on additional component data not shown.

Partition coefficient n-octanol / water (log Kow)

1,1-difluoroethane 0.75 Ethyl Alcohol -0.31

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable. Special precautions for user Not available.

Special provisions N82
Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

Packaging Exceptions LTD QTY

IMDG

UN number UN1950 UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) None

Packing group Not applicable.

Environmental hazards

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions
Transport in bulk according to
Annex II of MARPOL 73/78 and

Not applicable.

LTD QTY

Annex II of MARPO

the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

1,1-difluoroethane (CAS 75-37-6)

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

1,1-difluoroethane (CAS 75-37-6) Ethyl Alcohol (CAS 64-17-5)

US. New Jersey Worker and Community Right-to-Know Act

1,1-difluoroethane (CAS 75-37-6) Ethyl Alcohol (CAS 64-17-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethyl Alcohol (CAS 64-17-5)

US. Rhode Island RTK

1,1-difluoroethane (CAS 75-37-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

 Issue date
 08-10-2015

 Revision date
 02-26-2019

Version # 04

United States & Puerto Rico

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

Toxic Substances Control Act (TSCA) Inventory

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Hazard(s) identification: Response

Composition / Information on Ingredients: Component Summary

Regulatory information: California Prop 65

Product fiame. 14 02 GLAIRE ANTISTATIC SPRAY LB 12PK

Yes