



BIG ORANGE

ORANGE OIL TAR & ASPHALT REMOVER







DESCRIPTION

BIG ORANGE contains a natural orange oil solvent to quickly cut through tar, asphalt, gum, ink, crayon, tough soils, paint overspray and more. No chlorinated solvents, CFC's or other ozone depleting chemicals. No harmful or unpleasant fumes. Will soften some surfaces, including some plastics; use with care. If unsure of compatibility, test in an inconspicuous area prior to use.

APPLICATIONS

Use to remove tar, asphalt, gum, ink, crayon, tough soils, paint overspray and moren. Areas of use include homes, schools, detail services, offices, factories, convenience stores, hotels and motels.

FEATURES & BENEFITS

- · Cuts through a wide range of sticky soils
- · Non-chlorinated formula contains no ozone depleting chemicals
- · Pleasant orange fragrance

SPECIFICATIONS

ODOR: Citrus
COLOR: Clear
DETERGENCY: Excellent
TOXICITY: 1000 ppm OSHA TLV
WETTING ABILITY: Excellent
STORAGE STABILITY: 1 Year
COLD STABILITY: 32°F
PHOSPHATES: None

FORM: Solvent Based Aerosol

FLASH POINT: N/A
FLAME EXTENSION: <18"
SOLUBILITY IN WATER: 100%
SPECIFIC GRAVITY: 0.85
% VOLATILE BY VOLUME: 100%

pH: N/A

PROPELLANT: Hydrocarbon EVAPORATION RATE: Slow BIODEGRADABILITY: Yes

LABEL INFORMATION

BIG ORANGE ORANGE OIL TAR & ASPHALT REMOVER

VOC Content: 14.64%

BIG ORANGE contains a natural orange oil solvent to quickly cut through tar, asphalt, gum, ink, crayon, tough soils, paint overspray and more. The biodegradable formula leaves a fresh orange fragrance.

DIRECTIONS FOR USE: Shake well prior to use. Hold can 8-10 inches from surface, and spray to thoroughly wet area to be cleaned. Allow to penetrate a few minutes before rinsing. For heavy soil, a wire brush may be used to loosen accumulation. Always test in an inconspicuous area prior to use on any carpet, fabric or upholstery. Always rinse thoroughly. May be harmful to plastics. May stain some surfaces.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations.

CONTAINS (CAS#): Distillates (petroleum), hydrotreated light (64742-47-8), Methyl 9-Decenoate (25601-41-6), Nonionic Surfactant (127087-87-0), Nonylphenol Polyethoxylate (9016-45-9), Propane/Isobutane (68476-86-8).

HEALTH	1
FLAMMABILITY	3
REACTIVITY	1
PERSONAL	В



PACKAGING INFORMATION