

Revision Date: 10/21/2019

SAFETY DATA SHEET

1. Identification

Product identifier: TERAND BATTERY TERMINAL PROTECTOR

Other means of identification

SDS number: RE1000009129

Recommended restrictions

Product use: Coating

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name: CPC

Address: 1000 INTEGRAM DRIVE

PACIFIC, MO 63069

Telephone: 1-800-327-1835

Fax:

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Germ Cell Mutagenicity

Caregory 1B

Carcinogenicity

Category 1A

Specific Target Organ Toxicity - Category 1

Category 1

Category 1

Repeated Exposure

Aspiration Hazard Category 1

Target Organs

Nervous System

Environmental Hazards

Acute hazards to the aquatic Category 3

environment

Label Elements

Hazard Symbol:





Revision Date: 10/21/2019

Signal Word: Danger

Hazard Statement: Extremely flammable aerosol.

May cause genetic defects.

May cause cancer.

Causes damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Harmful to aquatic life.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the

environment.

Response: IF SWALLOWED: Immediately call a POISON CENTER/doctor Do NOT

induce vomiting. IF exposed or concerned: Get medical advice/attention.

Storage: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Butane	106-97-8	20 - <50%
Stoddard solvent	8052-41-3	20 - <50%
Naphtha (petroleum), light alkylate	64741-66-8	10 - <25%
Propane	74-98-6	10 - <20%
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	1 - <5%
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	1 - <5%
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	1 - <5%
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	1 - <5%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Rinse mouth. Call a physician or poison control center immediately. Never

give liquid to an unconscious person. If vomiting occurs, keep head low so

that stomach content doesn't get into the lungs.

Inhalation: Move to fresh air.



Revision Date: 10/21/2019

Skin Contact: Wash skin thoroughly with soap and water. Get medical attention if

symptoms occur.

Eye contact: Any material that contacts the eye should be washed out immediately with

water. If easy to do, remove contact lenses. If eye irritation persists: Get

medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: No data available.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a

protected location. Move containers from fire area if you can do so without

risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash

back.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep

upwind.

Methods and material for containment and cleaning

up:

Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

Notification Procedures: Prevent entry into waterways, sewer, basements or confined areas. Stop

the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you

can do so without risk.



Revision Date: 10/21/2019

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Wash hands thoroughly after handling. Do not handle until all safety

precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not

pierce or burn, even after use.

Conditions for safe storage, including any incompatibilities:

Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after

use. Aerosol Level 3

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit Values		Source	
Butane	REL	800 ppm	1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)	
	STEL	1,000 ppm		US. ACGIH Threshold Limit Values (03 2018)	
	TWA	800 ppm	1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)	
Stoddard solvent	TWA	100 ppm		US. ACGIH Threshold Limit Values (2008)	
	REL		350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)	
	PEL	500 ppm	2,900 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)	
	Ceil_Time		1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)	
	TWA	100 ppm	525 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)	
Propane	REL	1,000 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)	
	PEL	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)	
	TWA	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)	
Distillates (petroleum), hydrotreated heavy paraffinic - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)	
Distillates (petroleum), hydrotreated heavy paraffinic - Mist.	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)	
	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2016)	
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (01 2017)	
	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2016)	
Distillates (petroleum), solvent-dewaxed heavy paraffinic	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)	
	TWA	400 ppm	1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)	
Distillates (petroleum), solvent-dewaxed heavy paraffinic - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)	
•	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)	
	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)	
	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)	
Distillates (petroleum),	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)	



Revision Date: 10/21/2019

solvent-dewaxed heavy			
paraffinic - Inhalable fraction.			
Distillates (petroleum),	Ceil_Time	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards
solvent-dewaxed heavy		_	(2010)
paraffinic			
•	REL	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards
		222g	(2010)
Distillates (petroleum),	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards
hydrotreated light paraffinic -	1122	o mg/me	(2005)
Mist.			(2000)
	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards
			(2005)
	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
			, , , , ,
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants
			(29 CFR 1910.1000) (02 2006)
Distillates (petroleum),	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
hydrotreated light paraffinic -			
Inhalable fraction.			
Distillates (petroleum),	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards
solvent-dewaxed light		-	(2005)
paraffinic - Mist.			
1	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants
		- 3	(29 CFR 1910.1000) (02 2006)
	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL		US. NIOSH: Pocket Guide to Chemical Hazards
	KEL	5 mg/m3	
Distillator (autoriana)	T)4/4	5 / 0	(2005)
Distillates (petroleum),	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (01 2010)
solvent-dewaxed light			
paraffinic - Inhalable fraction.			

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

General information: Good general ventilation (typically 10 air changes per hour) should be used.

Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists,

mechanical generation of dusts, drying of solids, etc.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: No data available.

Other: Wear suitable protective clothing.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. When using do not smoke.

9. Physical and chemical properties

Appearance

Physical state: liquid

Form: Spray Aerosol
Color: No data available.
Odor: No data available.



Revision Date: 10/21/2019

Odor threshold:No data available.pH:No data available.Melting point/freezing point:No data available.Initial boiling point and boiling range:No data available.

Flash Point: -104.44 °C

Evaporation rate:No data available. **Flammability (solid, gas):**No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

No data available.

No data available.

No data available.

No data available.

Vapor pressure: 2,757.9029 - 4,136.8544 hPa (20 °C)

Vapor density:No data available.Density:No data available.Relative density:No data available.

Solubility(ies)

Solubility in water:

Solubility (other):

No data available.

No data available.

No data available.

No data available.

Auto-ignition temperature:No data available.Decomposition temperature:No data available.Viscosity:No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: No data available.

Hazardous Decomposition

Products:

No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation:No data available.Skin Contact:No data available.Eye contact:No data available.Ingestion:No data available.



Revision Date: 10/21/2019

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available. **Skin Contact:** No data available. **Eve contact:** No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Stoddard solvent LD 50: > 2,000 mg/kg

Naphtha (petroleum),

light alkylate

LD 50 (Rat): > 5,000 mg/kg

Distillates (petroleum), hydrotreated light

paraffinic

LD 50 (Rat): > 5,000 mg/kg

Distillates (petroleum),

solvent-dewaxed light

paraffinic

LD 50 (Rat): > 5,000 mg/kg

Distillates (petroleum), hydrotreated heavy

paraffinic

LD 50 (Rat): > 5,000 mg/kg

Distillates (petroleum), solvent-dewaxed heavy

paraffinic

LD 50 (Rat): > 5,000 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Stoddard solvent LD 50: > 2,000 mg/kg

Naphtha (petroleum),

light alkylate

LD 50 (Rabbit): > 6,000 mg/kg

Distillates (petroleum), hydrotreated light

paraffinic

LD 50 (Rabbit): > 5,000 mg/kg

Distillates (petroleum), solvent-dewaxed light

paraffinic

LD 50 (Rabbit): > 5,000 mg/kg

Distillates (petroleum), hydrotreated heavy

paraffinic

LD 50 (Rabbit): > 5,000 mg/kg

Distillates (petroleum), solvent-dewaxed heavy

paraffinic

LD 50 (Rabbit): > 2,000 mg/kg

Inhalation

Product: ATEmix: 13.39 mg/l



Revision Date: 10/21/2019

Repeated dose toxicity

Product: No data available.

Specified substance(s):

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Butane

Experimental result. Key study

NOAEL (Rat(Female, Male), Inhalation, >= 28 d); 4.000 ppm(m) Inhalation

Experimental result, Key study

NOAEL (Rat, Inhalation - vapor): 1.9 mg/l (Target Organ(s): Nervous Stoddard solvent

System)

NOAEL (Mouse, Rat(Female, Male), Inhalation, 107 - 113 Weeks): 1,402 Naphtha (petroleum),

mg/m3 Inhalation Experimental result, Key study light alkylate

NOAEL (Rat(Female, Male), Dermal, 5 - 28 d): 3,750 mg/kg Dermal

Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Propane

Experimental result, Key study

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result, Key study

Distillates (petroleum), hydrotreated light

NOAEL (Rat(Female, Male), Inhalation): 220 mg/m3 Inhalation Experimental

result, Key study

NOAEL (Rabbit(Female, Male), Dermal): 1,000 mg/kg Dermal Experimental paraffinic

result, Key study

LOAEL (Mouse(Male), Dermal, 24 Months): 100 mg/kg Dermal Experimental

result, Key study

Distillates (petroleum), solvent-dewaxed light

NOAEL (Rat(Female, Male), Inhalation): > 980 mg/m3 Inhalation Experimental result, Key study

LOAEL (Rat(Male), Oral, 13 Weeks): 125 mg/kg Oral Read-across from supporting substance (structural analogue or surrogate), Key study NOAEL (Rat(Female, Male), Dermal, 13 Weeks): >= 2,000 mg/kg Dermal

Experimental result, Key study

Distillates (petroleum),

hydrotreated heavy

paraffinic

paraffinic

NOAEL (Rat(Female, Male), Inhalation): > 980 mg/m3 Inhalation

Experimental result, Key study

LOAEL (Mouse(Male), Dermal, 24 Months): 100 mg/kg Dermal Experimental

result, Key study

NOAEL (Rat(Female, Male), Dermal, 13 Weeks): >= 2,000 mg/kg Dermal

Experimental result, Key study

Distillates (petroleum), solvent-dewaxed heavy

paraffinic

LOAEL (Rat(Male), Oral, 13 Weeks): 125 mg/kg Oral Read-across from supporting substance (structural analogue or surrogate), Key study NOAEL (Rat(Female, Male), Inhalation): 50 - 150 mg/m3 Inhalation

Experimental result, Supporting study

NOAEL (Rat(Female, Male), Inhalation): > 980 mg/m3 Inhalation

Experimental result, Key study

NOAEL (Rat(Female, Male), Dermal, 13 Weeks): < 30 mg/kg Dermal Readacross from supporting substance (structural analogue or surrogate), Key study

NOAEL (Rat, Inhalation): 500 mg/m3 Inhalation Experimental result,

Supporting study

Skin Corrosion/Irritation Product:

No data available.

Specified substance(s):

Naphtha (petroleum), light alkylate

In vitro (Human): not corrosive Experimental result, Supporting study

Distillates (petroleum), hydrotreated light

paraffinic

in vivo (Rabbit): Not irritant Experimental result, Key study



Revision Date: 10/21/2019

Distillates (petroleum), solvent-dewaxed light

in vivo (Rabbit): Not irritant Experimental result, Key study

paraffinic

Distillates (petroleum), hydrotreated heavy paraffinic

in vivo (Rabbit): Not irritant Experimental result, Key study

Distillates (petroleum), solvent-dewaxed heavy paraffinic

in vivo (Rabbit): Not irritant Experimental result, Kev study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Naphtha (petroleum), light alkylate

Rabbit, 24 - 72 hrs: Not irritating

Distillates (petroleum), hydrotreated light paraffinic

Rabbit, 48 hrs: Not irritating

Distillates (petroleum), solvent-dewaxed light

paraffinic

Rabbit, 48 hrs: Not irritating

Distillates (petroleum), hydrotreated heavy

paraffinic

Rabbit, 48 hrs: Not irritating

Distillates (petroleum), solvent-dewaxed heavy

paraffinic

Rabbit, 48 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Specified substance(s):

Naphtha (petroleum), light alkylate

Skin sensitization:, in vivo (Guinea pig): Non sensitising

Distillates (petroleum), hydrotreated light

Skin sensitization:, in vivo (Guinea pig): Non sensitising

paraffinic

Distillates (petroleum),

Skin sensitization:, in vivo (Guinea pig): Non sensitising

solvent-dewaxed light paraffinic

Distillates (petroleum), hydrotreated heavy

paraffinic

Skin sensitization:, in vivo (Guinea pig): Non sensitising

Distillates (petroleum), solvent-dewaxed heavy

Skin sensitization:, in vivo (Guinea pig): Non sensitising

paraffinic

Carcinogenicity

Product: No data available.

Specified substance(s):

Stoddard solvent Potential cancer hazard.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Distillates (petroleum), Overall evaluation: 3. Not classifiable as to carcinogenicity to humans.

hydrotreated light paraffinic



Revision Date: 10/21/2019

Distillates (petroleum), solvent-dewaxed light paraffinic

Overall evaluation: 3. Not classifiable as to carcinogenicity to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Distillates (petroleum), hydrotreated light paraffinic Distillates (petroleum), solvent-dewaxed light paraffinic

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

No data available. Product:

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: Nervous System - Causes damage to organs.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Target Organs

Specific Target Organ Toxicity - Repeated Exposure: Nervous System

Aspiration Hazard

Product: No data available.

Specified substance(s):

Stoddard solvent Naphtha (petroleum),

light alkylate

May be fatal if swallowed and enters airways. May be fatal if swallowed and enters airways.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study Butane

Naphtha (petroleum),

light alkylate

LL 50 (Oncorhynchus mykiss, 96 h): 10 mg/l Experimental result, Key study

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Distillates (petroleum),

hydrotreated light

paraffinic

LL 50 (Pimephales promelas, 96 h): > 100 mg/l Experimental result, Key

study

Distillates (petroleum),

solvent-dewaxed light

paraffinic

LL 50 (Pimephales promelas, 96 h): > 100 mg/l Experimental result, Key

study

SDS US - RE1000009129



Revision Date: 10/21/2019

Distillates (petroleum), hydrotreated heavy paraffinic LL 50 (Pimephales promelas, 96 h): > 100 mg/l Experimental result, Key

study

Distillates (petroleum), solvent-dewaxed heavy paraffinic LL 50 (Pimephales promelas, 96 h): > 100 mg/l Experimental result, Key

stud

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Butane LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study

Naphtha (petroleum), light alkylate

EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study NOAEL (Daphnia magna, 48 h): 0.5 mg/l Experimental result, Key study

Distillates (petroleum), hydrotreated light paraffinic EC 50 (Daphnia magna, 48 h): > 10,000 mg/l Experimental result, Key study

Distillates (petroleum), solvent-dewaxed light paraffinic

EC 50 (Daphnia magna, 48 h): > 10,000 mg/l Experimental result, Key study

Distillates (petroleum), hydrotreated heavy paraffinic

EC 50 (Daphnia magna, 48 h): > 10,000 mg/l Experimental result, Key study

Distillates (petroleum), solvent-dewaxed heavy paraffinic

EC 50 (Daphnia magna, 48 h): > 10,000 mg/l Experimental result, Key study

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Naphtha (petroleum), light alkylate

NOAEL (Pimephales promelas): 2.6 mg/l Experimental result, Supporting

study

Distillates (petroleum), hydrotreated light paraffinic

NOAEL (Oncorhynchus mykiss): >= 1,000 mg/l QSAR QSAR, Supporting

NOAEL (Oncorhynchus mykiss): >= 1,000 mg/l QSAR QSAR, Supporting

study

Distillates (petroleum), solvent-dewaxed light

study

paraffinic

Distillates (petroleum), hydrotreated heavy paraffinic NOAEL (Oncorhynchus mykiss): >= 1,000 mg/l QSAR QSAR, Supporting study

Distillates (petroleum), solvent-dewaxed heavy paraffinic

NOAEL (Oncorhynchus mykiss): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Naphtha (petroleum), light alkylate

NOAEL (Daphnia magna): 2.6 mg/l Experimental result, Key study

SDS US - RE1000009129



Revision Date: 10/21/2019

Distillates (petroleum), hydrotreated light paraffinic

NOAEL (Daphnia magna): 10 mg/l Experimental result, Key study

Distillates (petroleum), solvent-dewaxed light paraffinic

NOAEL (Daphnia magna): 10 mg/l Experimental result, Key study

Distillates (petroleum), hydrotreated heavy paraffinic

NOAEL (Daphnia magna): >= 1,000 mg/l Experimental result, Supporting

study

Distillates (petroleum), solvent-dewaxed heavy paraffinic

EC 50 (Daphnia magna): > 1,000 mg/l Experimental result, Supporting study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

Butane 100 % (385.5 h) Detected in water. Experimental result, Key study

Naphtha (petroleum), light alkylate

77.05 % Detected in water. Experimental result, Supporting study 90.35 % (28 d) Detected in water. Experimental result, Supporting study

Propane 100 % (385.5 h) Detected in water. Experimental result, Key study 50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Distillates (petroleum), hydrotreated light paraffinic

31 % (28 d) Detected in water. Experimental result, Supporting study 2 - 8 % (28 d) Detected in water. Experimental result, Supporting study

Distillates (petroleum), solvent-dewaxed light paraffinic

31 % (28 d) Detected in water. Experimental result, Supporting study 2 - 8 % (28 d) Detected in water. Experimental result, Supporting study

Distillates (petroleum), hydrotreated heavy paraffinic

2 - 8 % (28 d) Detected in water. Experimental result, Supporting study 31 % (28 d) Detected in water. Experimental result, Supporting study

Distillates (petroleum), solvent-dewaxed heavy paraffinic

2 - 8 % (28 d) Detected in water. Experimental result, Supporting study 31 % (28 d) Detected in water. Read-across based on grouping of substances (category approach), Supporting study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

No data available. Product:

Specified substance(s):

Naphtha (petroleum), light alkylate

Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by calculation, Key study

12/16

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Mobility in soil: No data available.

SDS US - RE1000009129



Revision Date: 10/21/2019

Known or predicted distribution to environmental compartments

Butane No data available. Stoddard solvent No data available. Naphtha (petroleum), light No data available.

alkylate

Propane No data available. Distillates (petroleum), No data available.

hydrotreated light paraffinic

Distillates (petroleum), solvent-dewaxed light

paraffinic

Distillates (petroleum),

hydrotreated heavy

paraffinic

Distillates (petroleum), solvent-dewaxed heavy

paraffinic

No data available.

No data available.

No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local

laws.

Contaminated Packaging: No data available.

14. Transport information

DOT

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2.1
Label(s): Packing Group: II
Marine Pollutant: No
Environmental Hazards: No
Marine Pollutant No

Special precautions for user: Not regulated.

IMDG

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2
Label(s): –
EmS No.:

Packing Group: -

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

IATA

UN Number: UN 1950

Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es):

Class: 2.1

SDS_US - RE1000009129



Revision Date: 10/21/2019

Label(s):

Packing Group: -

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

15. Regulatory information

US Federal Regulations

Restrictions on use: Not known.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u> <u>Reportable quantity</u>

Butane lbs. 100 Propane lbs. 100

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard

Delayed (Chronic) Health Hazard Immediate (Acute) Health Hazards

Flammable aerosol Germ Cell Mutagenicity

Carcinogenicity

Specific Target Organ Toxicity - Repeated Exposure

Aspiration Hazard

SARA 302 Extremely Hazardous Substance

Reportable

<u>Chemical Identity</u> <u>quantity</u> <u>Threshold Planning Quantity</u>

Stoddard solvent

SARA 304 Emergency Release Notification

Chemical Identity Reportable quantity

Butane lbs. 100

Stoddard solvent

Propane lbs. 100

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u> <u>Threshold Planning Quantity</u>

Butane 10000 lbs Stoddard solvent 10000 lbs Naphtha (petroleum), light 10000 lbs

alkylate

Propane 10000 lbs Distillates (petroleum), 10000 lbs

hydrotreated light

paraffinic

Distillates (petroleum), 10000 lbs

solvent-dewaxed light

paraffinic



Revision Date: 10/21/2019

Distillates (petroleum),

10000 lbs

hydrotreated heavy

paraffinic Distillates (petroleum),

10000 lbs

solvent-dewaxed heavy

paraffinic

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3) **US State Regulations**

US. California Proposition 65

No ingredient requiring a warning under CA Prop 65.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Butane

Stoddard solvent

Propane

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Distillates (petroleum), hydrotreated light paraffinic

Distillates (petroleum), solvent-dewaxed light paraffinic

US. Massachusetts RTK - Substance List

Chemical Identity

Distillates (petroleum), hydrotreated light paraffinic

Distillates (petroleum), solvent-dewaxed light paraffinic

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Butane

Stoddard solvent

Propane

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Distillates (petroleum), hydrotreated light paraffinic

Distillates (petroleum), solvent-dewaxed light paraffinic

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

Stoddard solvent

Stockholm convention

Stoddard solvent

Rotterdam convention

Stoddard solvent

Kyoto protocol



Revision Date: 10/21/2019

Inventory Status:

Australia AICS: On or in compliance with the inventory

Canada DSL Inventory List:

On or in compliance with the inventory

EINECS, ELINCS or NLP: Not in compliance with the inventory.

Japan (ENCS) List: Not in compliance with the inventory.

China Inv. Existing Chemical Substances: Not in compliance with the inventory.

Korea Existing Chemicals Inv. (KECI): Not in compliance with the inventory.

Canada NDSL Inventory: Not in compliance with the inventory.

Philippines PICCS: On or in compliance with the inventory

US TSCA Inventory: On or in compliance with the inventory

New Zealand Inventory of Chemicals: On or in compliance with the inventory

Japan ISHL Listing: Not in compliance with the inventory.

Japan Pharmacopoeia Listing: Not in compliance with the inventory.

Mexico INSQ: Not in compliance with the inventory.

Ontario Inventory: On or in compliance with the inventory

Taiwan Chemical Substance Inventory: On or in compliance with the inventory

16.Other information, including date of preparation or last revision

Issue Date: 10/21/2019

Revision Information: No data available.

Version #: 1.0

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.