

# SAFETY DATA SHEET

---

## SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

---

**Product ID:** 493905  
**Product Name:** ZenaZyme  
**Revision Date:** Jun 27, 2018 **Date Printed:** Jun 27, 2018  
**Version:** 1.0 **Supersedes Date:** Nov 15, 2016  
**Manufacturer's Name:** Zenex International  
**Address:** 1 Zenex Circle Cleveland, OH, US, 44146  
**Emergency Phone:** 1-800-535-5053  
**Information Phone Number:** (440)-232-4155  
**Fax:**  
**Product/Recommended Uses:** Upholstery Cleaner with Odor Counteractant

---

## SECTION 2) HAZARDS IDENTIFICATION

---

### Classification

Eye Irritation - Category 2B  
Gases Under Pressure Liquefied Gas

### Pictograms



### Signal Word

Warning

### Hazardous Statements - Physical

H280 - Contains gas under pressure; may explode if heated

### Hazardous Statements - Health

H320 - Causes eye irritation

### Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P103 - Read label before use.

### Precautionary Statements - Prevention

P264 - Wash hands thoroughly after handling.

### Precautionary Statements - Response

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 - If eye irritation persists: Get medical attention.

### Precautionary Statements - Storage

P410 + P403 - Protect from sunlight. Store in a well-ventilated place.

## Precautionary Statements - Disposal

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

---

### SECTION 3) COMPOSITION, INFORMATION ON INGREDIENTS

---

CAS	Chemical Name	% By Weight
0000074-98-6	PROPANE	1% - 4%
0000106-97-8	BUTANE	1% - 4%
0084133-50-6	Alcohols, C12-14-secondary, ethoxylated	0.1% - 3%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

---

### SECTION 4) FIRST-AID MEASURES

---

#### Inhalation

Remove to fresh air. Administer oxygen if needed. Apply artificial respiration if breathing has stopped. Get medical attention.

#### Eye Contact

Wash immediately with large volumes of fresh water for at least 15 minutes. Get medical attention.

#### Skin Contact

Wipe off with a towel. Wash with soap and water. Get medical attention if irritation persists.

#### Ingestion

Ingestion is not a likely route of exposure. Get medical attention if you feel unwell.

---

### SECTION 5) FIRE-FIGHTING MEASURES

---

#### Suitable Extinguishing Media

Foam, Alcohol foam, CO<sub>2</sub>, Dry Chemical, Water fog.

#### Unsuitable Extinguishing Media

Water may be ineffective but can be used to cool containers exposed to heat or flame.

#### Specific Hazards in Case of Fire

Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Liquid content of container will not support combustion. Overexposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain medical attention. Hazardous decomposition products include carbon dioxide, carbon monoxide, and other toxic fumes.

#### Fire-Fighting Procedures

Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat.

#### Special Protective Actions

Wear goggles and use a self-contained breathing apparatus. If water is used, fog nozzles are preferred.

---

### SECTION 6) ACCIDENTAL RELEASE MEASURES

---

#### Emergency Procedure

Avoid breathing vapors. Ventilate area. Remove all sources of ignition.

#### Recommended Equipment

Clean up with an absorbent material and place in closed containers for disposal.

### Personal Precautions

Avoid breathing vapors. Ventilate area. Wear safety glasses and gloves.

### Environmental Precautions

Stop spill/release if it can be done safely.

---

## SECTION 7) HANDLING AND STORAGE

---

### General

Do not puncture or incinerate (burn) cans. Do not stick pins, nails, or any other sharp objects into opening on top of can. Do not spray in eyes. Do not take internally.

### Ventilation Requirements

Use in a well ventilated place.

### Storage Room Requirements

Store and use in a cool, dry, well-ventilated area. Do not store above 120°F. See product label for additional information.

---

## SECTION 8) EXPOSURE CONTROLS, PERSONAL PROTECTION

---

### Eye Protection

Safety glasses with side shields should be used if indicated. Eye wash and safety showers in the workplace are recommended.

### Skin Protection

Use solvent-resistant protective gloves for prolonged or repeated contact.

### Respiratory Protection

In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use an approved air line respirator or hood. A self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

### Appropriate Engineering Controls

Ventilation should be sufficient to prevent inhalation of any vapors.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen
BUTANE								800	1900			
PROPANE	1000	1800			1			1000	1800			

Chemical Name	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)
BUTANE	1000			
PROPANE	See Appendix F: Minimal Oxygen Content			

(C) - Ceiling limit

---

**SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES**

---

**Physical and Chemical Properties**

Density	7.87143 lb/gal
Density VOC	0.31486 lb/gal
% VOC	4.00000%
<hr/>	
Appearance	N.A.
Odor Threshold	N.A.
Odor Description	Fresh
pH	9.5
Water Solubility	N.A.
Flammability	Flash point at or above 200°F/93°C
Flash Point Symbol	N.A.
Flash Point	N.A.
Viscosity	N.A.
Lower Explosion Level	N.A.
Upper Explosion Level	N.A.
Vapor Density	Slower than ether
Melting Point	N.A.
Freezing Point	N.A.
Low Boiling Point	N.A.
High Boiling Point	N.A.
Decomposition Pt	N.A.
Auto Ignition Temp	N.A.
Evaporation Rate	Slower than ether

---

**SECTION 10) STABILITY AND REACTIVITY**

---

**Stability**

The product is stable under normal storage conditions.

**Conditions to Avoid**

High temperatures.

**Incompatible Materials**

None known.

**Hazardous Reactions/Polymerization**

None known.

**Hazardous Decomposition Products**

Hazardous decomposition products may include carbon dioxide, carbon monoxide, and other toxic fumes.

---

**SECTION 11) TOXICOLOGICAL INFORMATION**

---

**Skin Corrosion/Irritation**

---

No data available

**Classification of the substance or mixture**

There is no toxicological data available for this product.

**Serious Eye Damage/Irritation**

Causes eye irritation

**Carcinogenicity**

No data available

**Germ Cell Mutagenicity**

No data available

**Reproductive Toxicity**

No data available

**Respiratory/Skin Sensitization**

No data available

**Specific Target Organ Toxicity - Single Exposure**

No data available

**Specific Target Organ Toxicity - Repeated Exposure**

No data available

**Aspiration Hazard**

No data available

**Acute Toxicity**

0000106-97-8 BUTANE

LC50 (mouse): 202000 ppm (481000 mg/m3) (4-hour exposure); cited as 680 mg/L (2-hour exposure) (9)

LC50 (rat): 276000 ppm (658000 mg/m3) (4-hour exposure); cited as 658 mg/L (4- hour exposure) (9)

---

**SECTION 12) ECOLOGICAL INFORMATION**

---

**Toxicity**

No data available

**Classification of the substance or mixture**

There is no ecological data available for this product.

**Persistence and Degradability**

No data available.

**Bio-Accumulative Potential**

No data available.

**Mobility in Soil**

No data available.

**Other Adverse Effects**

No data available.

## SECTION 13) DISPOSAL CONSIDERATIONS

---

### Water Disposal

Under RCRA, it is the responsibility of the user of the product, to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

---

## SECTION 14) TRANSPORT INFORMATION

---

### U.S. DOT Information

UN number: UN1950

Proper shipping name: Aerosols, non-flammable, (each not exceeding 1 L capacity) (LTD QTY)

Hazard class: 2.2

### IMDG Information

UN number: UN1950

Proper shipping name: Aerosols, non-flammable, (each not exceeding 1 L capacity) (LTD QTY)

Hazard class: 2.2

### IATA Information

UN number: UN1950

Hazard class: 2.2

Proper shipping name: Aerosols, non-flammable, (each not exceeding 1 L capacity) (N/A)

---

## SECTION 15) REGULATORY INFORMATION

---


CAS	Chemical Name	% By Weight	Regulation List
0000074-98-6	PROPANE	1% - 4%	SARA312,VOC,TSCA,ACGIH,OSHA
0000106-97-8	BUTANE	1% - 4%	SARA312,VOC,TSCA,ACGIH
0084133-50-6	Alcohols, C12-14-secondary, ethoxylated	0.1% - 3%	SARA312,TSCA

## SECTION 16) OTHER INFORMATION

### Glossary

\* There are points of differences between OSHA GHS and UN GHS. In 90% of the categories, they can be used interchangeably, but for the Skin Corrosion/Irritant Category and the Specific Target Organ Toxicity (Single and Repeated Exposure) Categories. In these cases, our system will say UN GHS.

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.



( \* ) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

### Version 1.0:

Revision Date: Jun 26, 2018

## DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.