



Version 2

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier Product name Chemical name	CHAMPION'S CHOICE CS+ LUBRICANT 7-7886-3
Other means of identification Product code	FG 438-5158-10
Synonyms	Multi-purpose Lubricant.
Recommended use of the chemical	and restrictions on use
Recommended Use	Stops annoying squeaks, guards against rust and corrosion, releases rusted or frozen
Uses advised against	metal parts, removes moisture. See directions for use on product's label.
Details of the supplier of the safety	data sheet
Supplier Address	Manufacturer Address
Chase Products Co. 2727 Gardner Road	Chase Products Co. 2727 Gardner Road
Broadview, IL 60155	Broadview, IL 60155
708-865-1000	708-865-1000
Emergency Telephone Number Company Phone Number 24 Hour Emergency Phone Number Emergency telephone	708-865-1000 1-800-255-3924 ChemTel 1-800-255-3924

2. Hazards Identification

Classification

Acute toxicity - Inhalation (Gases)	Category 3
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Aspiration toxicity	Category 1
FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	Compressed Gas

Label Elements

EMERGENCY OVERVIEW

DANGER

hazard statements Toxic if inhaled May be fatal if swallowed and enters airways EXTREMELY FLAMMABLE AEROSOL Contains gas under pressure; may explode if heated



Appearance Amber liquid.		Physical State Aerosol	Odor	Petroleum hydrocarbon odd
Precautionary Statements - Preva Avoid breathing fumes, mist, vapo Jse only outdoors or in a well-ven Keep away from heat, sparks, ope Pressurized container: Do not pier Do not spray on an open flame or	rs or spray. tilated area n flames and hot ce or burn, even a	after use		
Precautionary Statements - Res Specific treatment: See additional F INHALED: Remove victim to fre Call a POISON CENTER or docto F SWALLOWED: Immediately cal Do NOT induce vomiting	cautionary statem sh air and keep a r/physician	t rest in a position comfortable	e for breathing	
Precautionary Statements - Stor	-	the closed		
Store in a well-ventilated place. Ke Protect from sunlight. Do not expo Precautionary Statements - Disp	se to temperature	s exceeding 50 °C/122 °F		
Store in a well-ventilated place. Kee Protect from sunlight. Do not expo Dispose of contents/container to a <u>lazards not otherwise classifier</u> <u>Other Information</u> May be harmful in contact with sl Toxic to aquatic life with long las	se to temperature posal n approved waste d (HNOC) kin	s exceeding 50 °C/122 °F		
Store in a well-ventilated place. Kee Protect from sunlight. Do not expo Dispose of contents/container to a <u>dazards not otherwise classifier</u> <u>Dispose Information</u> May be harmful in contact with sl Toxic to aquatic life with long las	se to temperature posal n approved waste d (HNOC) kin ting effects	es exceeding 50 °C/122 °F		
Store locked up Store in a well-ventilated place. Ke Protect from sunlight. Do not expo Precautionary Statements - Disp Dispose of contents/container to a <u>Hazards not otherwise classifier</u> <u>Other Information</u> • May be harmful in contact with sl • Toxic to aquatic life with long last • Toxic to aquatic life	se to temperature posal n approved waste d (HNOC) kin ting effects	s exceeding 50 °C/122 °F	gredients	
Store in a well-ventilated place. Ke Protect from sunlight. Do not expo Precautionary Statements - Disp Dispose of contents/container to a <u>Hazards not otherwise classifier</u> <u>Dther Information</u> May be harmful in contact with sl Toxic to aquatic life with long las	se to temperature posal n approved waste d (HNOC) kin ting effects	e disposal plant i tion/information on In	gredients	
Store in a well-ventilated place. Ke Protect from sunlight. Do not expo Precautionary Statements - Disp Dispose of contents/container to a <u>lazards not otherwise classifier</u> <u>Dispose of contents/container to a</u> <u>lazards not otherwise classifier</u> <u>Dispose of contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/contents/conten</u>	se to temperature posal n approved waste d (HNOC) kin ting effects 3. Compos Multi-purpos MIXTURES. 7-7886-3	e disposal plant ition/information on In e Lubricant.		Trade secret
Expression a well-ventilated place. Kee Protect from sunlight. Do not expo Precautionary Statements - Disp Dispose of contents/container to a lazards not otherwise classifier Dispose of contents/container to a lazards notherwise classifier Dispose of contents/container to lazar	se to temperature posal n approved waste d (HNOC) kin ting effects 3. Compos Multi-purpos MIXTURES. 7-7886-3	e disposal plant i tion/information on In	gredients weight-% 40-45	Trade secret
Expression a well-ventilated place. Kee Protect from sunlight. Do not expo Precautionary Statements - Disp Dispose of contents/container to a lazards not otherwise classifier Differ Information May be harmful in contact with sl Toxic to aquatic life with long last Toxic to aquatic life Synonyms Chemical Family Formula Chemical name Petroleum distillates, hydro	se to temperature posal n approved waste d (HNOC) kin ting effects 3. Compos Multi-purpos MIXTURES. 7-7886-3 treated light	e disposal plant ition/information on In se Lubricant. CAS No 64742-47-8	weight-% 40-45	Trade secret
tore in a well-ventilated place. Ke protect from sunlight. Do not expo precautionary Statements - Disp pispose of contents/container to a lazards not otherwise classifier other Information May be harmful in contact with sl Toxic to aquatic life with long last Toxic to aquatic life Synonyms chemical Family formula Chemical name Petroleum distillates, hydro Hydrotreated Heavy Naph	se to temperature posal n approved waste d (HNOC) kin ting effects 3. Compos Multi-purpos MIXTURES. 7-7886-3 treated light thenic Oil	s exceeding 50 °C/122 °F e disposal plant sition/information on In se Lubricant. CAS No 64742-47-8 64742-52-5	weight-% 40-45 40-45	*
Store in a well-ventilated place. Kee Protect from sunlight. Do not expo Precautionary Statements - Disp Dispose of contents/container to a Hazards not otherwise classifier Date Information May be harmful in contact with sl Toxic to aquatic life with long last Toxic to aquatic life Synonyms Chemical Family Formula Chemical name Petroleum distillates, hydro	se to temperature posal n approved waste d (HNOC) kin ting effects 3. Compos Multi-purpos MIXTURES. 7-7886-3 treated light thenic Oil pirits	e disposal plant ition/information on In se Lubricant. CAS No 64742-47-8	weight-% 40-45	*

4. First aid measures

FIRST AID MEASURES

Eye Contact	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
Skin contact	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advise.
Inhalation	If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an ambulance, then provide artifical respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advise.

Ingestion	Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates. Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician immediately.			
Most important symptoms and effects, both acute and delayed				
Symptoms	Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness and nausea. Prolonged and repeated contact with skin may cause irritation and reddening. Contact with eyes causes irritation.			
Indication of any immediate medica	al attention and special treatment needed			
Note to physicians	Contains petroleum distillates, do not induce vomiting because of aspiration neumonia hazard.			
5. Fire-fighting measures				

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may release carbon monoxide and carbon dioxide.

Explosion data

Sensitivity to Mechanical Impac	t Contents under pressure. This product is extremely flammable. Keep away from heat,
	sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static
	electricity).
Sensitivity to Static Discharge	Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric
	motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an appropriate, properly fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully for respirator use.	
For emergency responders	Remove all sources of ignition.	
Environmental precautions		
Environmental precautions	See Section 12 for additional Ecological Information.	
Methods and material for containm	nent and cleaning up	
Methods for Containment	Provide adequate ventilation to area being treated. Soak up spills with chemically inert,	

	absorbent material.	
Methods for cleaning up	Clean contaminated surface thoroughly.	
7. Handling and Storage		
Precautions for safe handling		
Advice on safe handling	Handle as an extremely flammable material. Avoid contact with skin, eyes and clothing. Store cans in a cool, dry place away from heat and open flame.	
Conditions for safe storage, includ	ing any incompatibilities	
Storage Conditions	Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). AEROSOL STORAGE LEVEL III (NFPA-30B).	
Incompatible Materials	Avoid heat, open flame and contact with strong acids, strong bases and strong oxidizers.	
	8. Exposure Controls/Personal Protection	

Control parameters

Exposure guidelines

See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Carbon Dioxide	STEL: 30000 ppm	TWA: 5000 ppm	IDLH: 40000 ppm
124-38-9	TWA: 5000 ppm	TWA: 9000 mg/m ³	TWA: 5000 ppm
		(vacated) TWA: 10000 ppm	TWA: 9000 mg/m ³
		(vacated) TWA: 18000 mg/m ³	STEL: 30000 ppm
		(vacated) STEL: 30000 ppm	STEL: 54000 mg/m ³
		(vacated) STEL: 54000 mg/m ³	
Petroleum distillates (naphtha)	-	TWA: 500 ppm	IDLH: 1100 ppm
8002-05-9		TWA: 2000 mg/m ³	Ceiling: 1800 mg/m ³ 15 min
		(vacated) TWA: 400 ppm	TWA: 350 mg/m ³
		(vacated) TWA: 1600 mg/m ³	_

Appropriate engineering controls

Engineering controls Use with adequate general or local exhaust ventilation. Use in a well-ventilated area only.

Individual protection measures, such as personal protective equipment

Eye/face Protection	Conventional eyeglasses to guard against splashing.
Skin and Body Protection	Neoprene or rubber gloves required.

Respiratory protection Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an appropriate, properly fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully for respirator use.

General hygiene considerations Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State

```
Aerosol
```

FG 438-5158-10 CHAMPION'S CHOICE CS+ LUBRICANT

Appearance	Amber liquid.	Odor	Petroleum hydrocarbon odor.
Color	Amber liquid.	Odor threshold	No information available
<u>Property</u> pH Melting point/freezing point Boiling point/boiling range Flash Point	<u>Values</u> Not applicable Not applicable Petroleum Distillate >433 °F/>223 °C Not Available. This is an aerosol product for which Flame Projection is over 18 inches with 1 inches flashback Temperatures above 120 F may cause cans to burst.		
Evaporation Rate Flammability (solid, gas) Flammability Limits in Air Upper flammability limits Lower Flammability Limit Vapor pressure Vapor Density Relative Density Water solubility Solubility in other solvents Partition coefficient Autoignition Temperature Decomposition temperature	Faster than butyl acetate Not available Not available 0.850 concentrate Insoluble in water	No information available No information available	
Kinematic viscosity Dynamic viscosity Explosive properties Oxidizing properties <u>Other Information</u>	No information available No information available	No information available No information available	
Softening point Molecular weight VOC content (%) Density Bulk Density	No information available No information available 9.60 7.08 lb/gal No information available		
	10 Stability and Poact	1	

10. Stability and Reactivity

Reactivity Not applicable

No data available

Chemical stability Stable.

Possibility of hazardous reactions Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization

Hazardous polymerization does not occur.

Conditions to Avoid Temperatures above 122 °F (50 °C).

Incompatible Materials

Avoid heat, open flame and contact with strong acids, strong bases and strong oxidizers.

Hazardous decomposition products

Thermal decomposition may release carbon monoxide and carbon dioxide.

11. Toxicological Information

Information on likely routes of exposure

 Product Information
 This product has not been tested as whole. See below for information on ingredients.

 Inhalation
 No data available.

 Eye Contact
 No data available.

 Skin contact
 No data available.

 Ingestion
 No data available.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat)4 h
Hydrotreated Heavy Naphthenic Oil 64742-52-5	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
Low Odor Mineral Spirits 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat)4 h
Petroleum distillates (naphtha) 8002-05-9	> 4300 mg/kg (Rat)> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-

Information on toxicological effects

Symptoms

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationMay cause skin irritation and reddening after prolonged or repeated contact with skin.Serious eye damage/eye irritationIrritating to eyes.irritationMay cause skin and eye irritation.corrosivityNot applicable.sensitizationMay cause sensitization of susceptible persons.Germ cell mutagenicityNot information available.CarcinogenicityNot known chronic effects based on available information. The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Hydrotreated Heavy	A2	Group 1	Known	Х
Naphthenic Oil				
64742-52-5				
Petroleum distillates	A2	Group 1	Known	Х
(naphtha)		Group 3		
8002-05-9				

Reproductive toxicity STOT - single exposure STOT - repeated exposure Aspiration Hazard No information available. No information available. No information available. No information available.

Numerical measures of toxicity - Product Information

 Unknown acute toxicity

 The following values are calculated based on chapter 3.1 of the GHS document .

 ATEmix (oral)
 9390 mg/kg

 ATEmix (dermal)
 3756 mg/kg

 ATEmix (inhalation-gas)
 981 mg/l

 ATEmix (inhalation-dust/mist)
 4 mg/l

 ATEmix (inhalation-vapor)
 9.8 mg/l

12. Ecological Information

ecotoxicity

6.1 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Petroleum distillates, hydrotreated light 64742-47-8		2.2: 96 h Lepomis macrochirus mg/L LC50 static 45: 96 h Pimephales promelas mg/L LC50 flow-through 2.4: 96 h Oncorhynchus mykiss mg/L		4720: 96 h Den-dronereides heteropoda mg/L LC50
Hydrotreated Heavy Naphthenic Oil 64742-52-5		LC50 static 5000: 96 h Oncorhynchus mykiss mg/L LC50		1000: 48 h Daphnia magna mg/L EC50
Low Odor Mineral Spirits 64742-47-8		2.2: 96 h Lepomis macrochirus mg/L LC50 static 45: 96 h Pimephales promelas mg/L LC50 flow-through 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static		4720: 96 h Den-dronereides heteropoda mg/L LC50
Petroleum distillates (naphtha) 8002-05-9		258: 96 h Salmo gairdneri mg/L LC50 static		36: 24 h Daphnia magna mg/L EC50 0.26: 48 h Daphnia magna mg/L EC50 Static

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Other adverse effects

No information available

13. Disposal Considerations

Waste treatment methods

Disposal of wastes Dispose of in accordance with federal, state and local regulations.

Contaminated packaging Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions.

14. Transport Information

DOT

UN/ID no Proper Shipping Name Hazard Class Limited Quantity Consumer Commodity 2.2

<u>IATA</u>

UN/ID no	UN1950
Proper Shipping Name	Aerosols, flammable
Hazard Class	2.2

IMDG

UN/ID no	UN1950
Proper Shipping Name	Aerosols, flammable
Hazard Class	2.2
Marine pollutant	This product does not contain marine pollutants.

15. Regulatory information

International Inventories TSCA

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Subtances Control Act (TSCA) Chemical Substance Inventory. All ingredients are listed or are excluded from listing on the DSL.

DSL

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

This product does not contain toxic chemicals (above the de minimis level) subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
Petroleum distillates (naphtha) - 8002-05-9	8002-05-9	<1	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	No
Fire Hazard	yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Carbon Dioxide	Х	Х	Х
124-38-9			
Petroleum distillates (naphtha)	Х	X	X

8002-05-9

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information				
NFPA_	Health Hazards 2	Flammability 4	Instability 1	Physical and chemical properties Not applicable
<u>HMIS</u>	Health Hazards 2	Flammability 4	Physical hazards 1	Personal Protection B - Eyes and hands protection
Prepared by Issue date Revision note	-	Regulatory Department 03-Apr-2019		
This SDS supersedes a previous SDS dated August 17, 2015. <u>Disclaimer</u>				

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet