

# **Safety Data Sheet**

Issue date 11-Jan-2021 Version 2

# 1. Identification of the Substance/Preparation and of the Company/Undertaking

**Product Identifier** 

Product name CHAMPION'S CHOICE PENETRATING OIL AND DEMOISTURANT

Chemical name 7-7708-3

Other means of identification

Product code FG 438-5159-5

**Synonyms** Penetrating oil and demoisturant.

Recommended use of the chemical and restrictions on use

Recommended Use Stops annoying squeaks, guards against rust and corrosion, releases rusted or frozen

metal parts, removes moisture.

**Uses advised against** See directions for use on product's label.

Details of the supplier of the safety data sheet

Supplier Address
Chase Products Co.
2727 Gardner Road
Broadview, IL 60155
708-865-1000

Manufacturer Address
Chase Products Co.
2727 Gardner Road
Broadview, IL 60155
708-865-1000

708-865-1000

**Emergency Telephone Number** 

**Company Phone Number** 708-865-1000 **24 Hour Emergency Phone Number** 1-800-255-3924

Emergency telephone ChemTel 1-800-255-3924

# 2. Hazards Identification

### Classification

Acute toxicity - Inhalation (Gases)	Category 4
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1
Gases Under Pressure	liquefied gas

# **Label Elements**

#### **EMERGENCY OVERVIEW**

# DANGER

# hazard statements

HARMFUL IF INHALED

May cause cancer

Causes damage to organs through prolonged or repeated exposure

Contains gas under pressure; may explode if heated



Appearance Dark brown liquid. Physical State Aerosol Odor Chlorinated solvent odor

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves, protective clothing, eye protection and face protection.

Use only outdoors or in a well-ventilated area

Do not breathe fumes, mist, vapors or spray.

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

#### **Precautionary Statements - Response**

IF exposed: Call a POISON CENTER or doctor/physician

Specific treatment: See additional cautionary statements on this label.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell

### **Precautionary Statements - Storage**

Store locked up

Protect from sunlight. Store in a well-ventilated place

# **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

#### Other Information

· Toxic to aquatic life with long lasting effects

7.67% of the mixture consists of ingredient(s) of unknown toxicity

# 3. Composition/information on Ingredients

**Synonyms** Penetrating oil and demoisturant.

Chemical FamilyMIXTURES.Formula7-7708-3

Chemical name	CAS No	weight-%	Trade secret
Tetrachloroethylene	127-18-4	60-65	*
Hydrotreated Heavy Naphthenic Oil	64742-52-5	15-20	*
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	5-10	*
Chloroalkanes	68920-70-7	1-5	*
Chlorinated Paraffin	63449-39-8	1-5	*
Calcium Sulfonate	61789-86-4	1-5	*
Carbon Dioxide	124-38-9	1-5	*
2-Butoxyethanol	111-76-2	1-5	*

<sup>\*</sup> The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. First aid measures

### **FIRST AID MEASURES**

Eye Contact Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact

lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control

center or doctor for treatment advice.

**Skin contact**Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20

minutes. Call a poison control center or doctor for treatment advise.

**Inhalation** If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an

ambulance, then provide artifical respiration, preferably mouth-to-mouth, if possible. Call a

poison control center or doctor for further treatment advise.

Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates. Ingestion

Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician

immediately.

Most important symptoms and effects, both acute and delayed

**Symptoms** Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness

and nausea. Prolonged and repeated contact with skin may cause irritation and reddening.

Contact with eyes causes irritation.

Indication of any immediate medical attention and special treatment needed

Contains petroleum distillates, do not induce vomiting because of aspiration neumonia Note to physicians

hazard.

# 5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

**Unsuitable extinguishing media** Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrogen

chloride, chlorine and traces of phogene.

**Explosion data** 

Sensitivity to Mechanical Impact Contents under pressure, keep away from heat and open flame.

Sensitivity to Static Discharge

Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and

> prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an appropriate, properly

fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator

manufacturer's instructions carefully for respirator use.

For emergency responders Remove all sources of ignition.

**Environmental precautions** 

**Environmental precautions** See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert,

absorbent material.

Methods for cleaning up Clean contaminated surface thoroughly.

# 7. Handling and Storage

Precautions for safe handling

Advice on safe handling Avoid contact with skin. Avoid getting spray into eyes. Do not deliberately inhale vapor or

mist. Do not contaminate food or food handling surfaces. Keep out of reach of children.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. AEROSOL STORAGE

LEVEL I (NFPA-30B).

Incompatible Materials Avoid heat, open flame and contact with strong acids, strong bases and strong oxidizers.

# 8. Exposure Controls/Personal Protection

#### Control parameters

**Exposure guidelines** See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Tetrachloroethylene	STEL: 100 ppm	TWA: 100 ppm	IDLH: 150 ppm
127-18-4	TWA: 25 ppm	(vacated) TWA: 25 ppm	
		(vacated) TWA: 170 mg/m <sup>3</sup>	
		Ceiling: 200 ppm	
Carbon Dioxide	STEL: 30000 ppm	TWA: 5000 ppm	IDLH: 40000 ppm
124-38-9	TWA: 5000 ppm	TWA: 9000 mg/m <sup>3</sup>	TWA: 5000 ppm
		(vacated) TWA: 10000 ppm	TWA: 9000 mg/m <sup>3</sup>
		(vacated) TWA: 18000 mg/m <sup>3</sup>	STEL: 30000 ppm
		(vacated) STEL: 30000 ppm	STEL: 54000 mg/m <sup>3</sup>
		(vacated) STEL: 54000 mg/m <sup>3</sup>	
2-Butoxyethanol	TWA: 20 ppm	TWA: 50 ppm	IDLH: 700 ppm
111-76-2		TWA: 240 mg/m <sup>3</sup>	TWA: 5 ppm
		(vacated) TWA: 25 ppm	TWA: 24 mg/m <sup>3</sup>
		(vacated) TWA: 120 mg/m <sup>3</sup>	
		(vacated) S*	
		S*	

# **Appropriate engineering controls**

### Individual protection measures, such as personal protective equipment

**Eye/face Protection** Conventional eyeglasses to guard against splashing.

**Skin and Body Protection** Polyvinyl alcohol or rubber gloves required.

**Respiratory protection** Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and

prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an appropriate, properly

fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully for respirator use.

manufacture of monactions carefully for recognition assets

General hygiene considerations Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Do not

eat, drink or smoke when using this product.

# 9. Physical and Chemical Properties

### Information on basic physical and chemical properties

Physical State Aerosol

AppearanceDark brown liquid.OdorChlorinated solvent odorColorDark brown liquidOdor thresholdNo information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pHNot applicableSolvent-based product.Melting point/freezing pointNot applicableNo information availableBoiling point/boiling rangePerchloroethyle 250 °F/121 °CNo information availableFlash PointNot Available. This is an aerosolNo information available

product for which Flame Projection is 0 inches. Temperatures above 120 °F may cause cans to burst. Not

applicable

**Evaporation Rate** Faster than butyl acetate No information available

Flammability (solid, gas) NA No information available Flammability Limits in Air No information available

Upper flammability limits

Not available

Lower Flammability Limit Not available

Vapor pressureNo information availableVapor DensityNo information available

Relative Density

1.29 - 1.33 concentrate

No information available

No information available

No information available

No information available

Solubility in other solventsNo information availablePartition coefficientNo information availableAutoignition TemperatureNo information availableDecomposition temperatureNo information available

Kinematic viscosity

No information available

Pynamic viscosity

No information available

Explosive propertiesNo information availableOxidizing propertiesNo information available

Other Information

Softening pointNo information availableMolecular weightNo information available

**VOC content (%) 3.81 Density 10.91** b/gal

Bulk Density No information available

# 10. Stability and Reactivity

Reactivity

Not applicable No data available

**Chemical stability** 

Stable.

Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

**Conditions to Avoid** 

Temperatures above 122 °F (50 °C).

### **Incompatible Materials**

Avoid heat, open flame and contact with strong acids, strong bases and strong oxidizers.

#### **Hazardous decomposition products**

Thermal decomposition may yield gases like carbon monoxide, carbon dioxide, hydrogen chloride, chlorine and traces of phogene.

# 11. Toxicological Information

### Information on likely routes of exposure

**Product Information**This product has not been tested as whole. See below for information on ingredients.

**Inhalation** No data available.

Eye Contact No data available.

**Skin contact** No data available.

**Ingestion** No data available.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Tetrachloroethylene 127-18-4	= 2629 mg/kg (Rat)	-	= 27.8 mg/L (Rat) 4 h
Hydrotreated Heavy Naphthenic Oil 64742-52-5	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
Solvent naphtha (petroleum), medium aliphatic 64742-88-7	> 25 mL/kg(Rat)	> 3000 mg/kg(Rabbit)	> 13 mg/L (Rat)4 h
Chlorinated Paraffin 63449-39-8	= 26100 mg/kg(Rat)> 21500 µL/kg (Rat)	> 10 mL/kg(Rabbit)	-
Calcium Sulfonate 61789-86-4	> 20 g/kg (Rat)	> 5000 mg/kg (Rabbit)	-
2-Butoxyethanol 111-76-2	= 470 mg/kg (Rat)	= 99 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h = 486 ppm Rat) 4 h

#### Information on toxicological effects

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation**May cause skin irritation and reddening after prolonged or repeated contact with skin.

Serious eye damage/eye irritation Irritating to eyes.

irritation May cause skin and eye irritation.

**corrosivity** Not applicable.

sensitization May cause sensitization of susceptible persons.

Germ cell mutagenicity No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Tetrachloroethylene 127-18-4	A3	Group 2A	Reasonably Anticipated	Х
Hydrotreated Heavy Naphthenic Oil 64742-52-5	A2	Group 1	Known	Х
Chloroalkanes 68920-70-7		Group 2B		Х
Chlorinated Paraffin 63449-39-8		Group 2B		Х
2-Butoxyethanol 111-76-2	A3	Group 3		

Reproductive toxicity No information available.

STOT - single exposure
STOT - repeated exposure
Aspiration Hazard
No information available.
No information available.

Numerical measures of toxicity - Product Information

**Unknown acute toxicity** 7.67% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 3463 mg/kg
ATEmix (dermal) 24717 mg/kg
ATEmix (inhalation-gas) 2602 mg/l
ATEmix (inhalation-dust/mist) 9.6 mg/l
ATEmix (inhalation-vapor) 30 mg/l

# 12. Ecological Information

This product contains chemicals which are listed as a marine pollutants according to DOT.

### ecotoxicity

6.1 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Tetrachloroethylene 127-18-4	500: 96 h Pseudokirchneriella subcapitata mg/L EC50	12.4 - 14.4: 96 h Pimephales promelas mg/L LC50 flow-through 8.6 - 13.5: 96 h Pimephales promelas mg/L LC50 static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 4.73 - 5.27: 96 h Oncorhynchus mykiss mg/L LC50 flow-through	EC50 = 100 mg/L 24 h EC50 = 112 mg/L 24 h EC50 = 120.0 mg/L 30 min	6.1 - 9.0: 48 h Daphnia magna mg/L EC50 Static
Hydrotreated Heavy Naphthenic Oil 64742-52-5		5000: 96 h Oncorhynchus mykiss mg/L LC50		1000: 48 h Daphnia magna mg/L EC50
Solvent naphtha (petroleum), medium aliphatic 64742-88-7	450: 96 h Pseudokirchneriella subcapitata mg/L EC50	800: 96 h Pimephales promelas mg/L LC50 static		100: 48 h Daphnia magna mg/L EC50
Chlorinated Paraffin 63449-39-8		300: 96 h Lepomis macrochirus mg/L LC50 static 100: 96 h Pimephales promelas mg/L LC50 static 0.1: 96 h Lepomis macrochirus mg/L LC50 flow-through 0.0109: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 94.5 - 271: 96 h Oncorhynchus mykiss mg/L LC50 static		102: 24 h Daphnia magna mg/L EC50
Calcium Sulfonate 61789-86-4		5.7 - 9.7: 96 h Pimephales promelas mg/L LC50 static 1.0 - 10.0: 96 h Pimephales promelas mg/L LC50 semi-static		6.2 - 12: 48 h Daphnia magna mg/L EC50
2-Butoxyethanol 111-76-2		1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50		1698 - 1940: 24 h Daphnia magna mg/L EC50 1000: 48 h Daphnia magna mg/L EC50

# Persistence and degradability

See table below.

# **Bioaccumulation**

No information available.

Chemical name	Partition coefficient
Tetrachloroethylene 127-18-4	2.53 - 2.88
Chlorinated Paraffin 63449-39-8	>6
2-Butoxyethanol 111-76-2	0.81

Other adverse effects

No information available

# 13. Disposal Considerations

#### Waste treatment methods

**Disposal of wastes**Dispose of in accordance with federal, state and local regulations.

Contaminated packaging Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate

container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your

local solid waste agency for disposal instructions.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Tetrachloroethylene	U210	Included in waste streams:	0.7 mg/L regulatory level	U210
127-18-4		F001, F002, F024, F025,		
		F039, K016, K019, K020,		
		K073, K116, K150, K151		

Chemical name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Tetrachloroethylene	Category I - Volatiles		Toxic waste	
127-18-4			waste number F025	
			Waste description:	
			Condensed light ends, spent	
			filters and filter aids, and	
			spent desiccant wastes from	
			the production of certain	
			chlorinated aliphatic	
			hydrocarbons, by free	
			radical catalyzed processes.	
			These chlorinated aliphatic	
			hydrocarbons are those	
			having carbon chain lengths	
			ranging from one to and	
			including five, with varying	
			amounts and positions of	
			chlorine substitution.	

Chemical name	California Hazardous Waste Status
Tetrachloroethylene	Toxic
127-18-4	

# 14. Transport Information

DOT

UN/ID no
Limited Quantity
Proper Shipping Name
Consumer Commodity
OPM D

Hazard Class ORM-D

Marine pollutant This product contains chemicals which are listed as a marine pollutants according to DOT.

IATA

UN/ID no UN1950

**Proper Shipping Name** Aerosols, non-flammable.

Hazard Class 2.2

**IMDG** 

UN/ID no UN1950
Proper Shipping Name Aerosols
Hazard Class 2

Marine pollutant This product contains chemicals that are listed as marine pollutants.

# 15. Regulatory information

**International Inventories** 

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic

Subtances Control Act (TSCA) Chemical Substance Inventory.

**DSL** All ingredients are listed or are excluded from listing on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

# **US Federal Regulations**

### **SARA 313**

This product contains the following toxic chemicals (above the de minimis level) subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
Tetrachloroethylene - 127-18-4	127-18-4	60-65	0.1
2-Butoxyethanol - 111-76-2	111-76-2	1-5	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard yes
Chronic Health Hazard yes
Fire Hazard No
Sudden release of pressure hazard No
Reactive Hazard No

#### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Tetrachloroethylene 127-18-4		X	X	

### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Tetrachloroethylene	100 lb 1 lb		RQ 100 lb final RQ
127-18-4			RQ 45.4 kg final RQ RQ 1 lb final
			RQ
			RQ 0.454 kg final RQ

### **US State Regulations**

### **California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65	
Tetrachloroethylene - 127-18-4	Carcinogen	

### **U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
Tetrachloroethylene 127-18-4	Х	X	X
Chlorinated Paraffin 63449-39-8		X	
Carbon Dioxide 124-38-9	Х	X	X
2-Butoxyethanol 111-76-2	Х	X	X

#### U.S. EPA Label information

**EPA Pesticide registration number** Not applicable

16. Other information						
NFPA_	Health Hazards 2	Flammability 1	Instability 1	Physical and chemical properties Not applicable		
HMIS	Health Hazards 2*	Flammability 1	Physical hazards 1	Personal Protection B - Eyes and hands protection		
Chronic Hazard Star Lege	nd See Section	n 11: TOXICOLOGICAL INF	FORMATION	•		

Prepared by Regulatory Department

Issue date 11-Jan-2021

**Revision note** 

This SDS supersedes a previous SDS dated May 26, 2015.

**Disclaimer** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**